

# SMT Series Connectors

## **D-SUB RIGHT ANGLE SURFACE - MOUNT CONNECTORS**

### **Specification :**

Contact Resistance : 30m $\Omega$ [Max. At DC 100mA  
Insulator Resistance : 1000M $\Omega$ [Min. At DC 500V  
Current Rating : 5 AMP

### **Dielectric Withstanding**

Voltage : AC 1000V For 1 Minute  
Operating Temperature : -55  $\phi$ XC ~ + 105  $\phi$ XC  
Contact : Brass Or Phosphor Bronze  
Housing : PBT & 30% Glass Fiber (UL 94V-0)



## **D-SUB HD RIGHT ANGLE SURFACE-MOUNT CONNECTORS**

### **Specification :**

Contact Resistance : 30m $\Omega$ [Max. At DC 100mA  
Insulator Resistance : 1000M $\Omega$ [Min. At DC 500V  
Current Rating : 5 AMP

### **Dielectric Withstanding**

Voltage : AC 1000V For 1 Minute  
Operating Temperature : -55  $\phi$ XC ~ + 105  $\phi$ XC  
Contact : Brass Or Phosphor Bronze  
Housing : PBT & 30% Glass Fiber (UL 94V-0)



*For ordering information please consult our sales department*